

Specifications

Model type	SR 110-36P	SR 90-36P	SR 85-36P	SR 80-36P	SR 75-36P	SR 70-36P
Peak power(Pmax)	110W	90W	85W	80W	75W	70W
Weight	9.18kg	7.76kg	7.35kg	7.02kg	6.62kg	6.29kg
Dimensions(mm)	1170x670x35	975x670x35	920x670x35	875x670x35	820x670x35	775x670x35
Maximum power voltage (Vmp)	17.5V	17.5V	17.5V	17.5V	17.5V	17.5V
Maximum power current (Imp)	6.29A	5.143A	4.86A	4.58A	4.29A	4A
Open circuit voltage (Voc)	21.6V	21.6V	21.6V	21.6V	21.6V	21.6V
Short circuit current (Isc)	7.10A	5.81A	5.49A	5.17A	4.84A	4.52A
Cell efficiency	16.50%	16.50%	16.50%	16.50%	16.50%	16.50%
Maximum system voltage	DC 1000V					
Temp.Coeff.of Isc(TK Isc)	0.045%/°C					
Temp.Coeff.of Voc(TK Voc)	-0.34%/°C					
Temp.Coeff.of Pmax(TK Pmax)	-0.47%/°C					
Normal Operating Cell Temperature	45±2°C					
Tolerance	±3%					

STC Irradiance 1000W/m² , Temperature 25°C , AM=1.5

Specifications

Model type	SR 60-36P	SR 55-36P	SR 50-36P	SR 45-36P	SR 40-36P	SR 30-36P
Peak power(Pmax)	60W	55W	50W	45W	40W	30W
Weight	5.52kg	5.19kg	4.82kg	4.42kg	4.09kg	3.36kg
Dimensions(mm)	675x670x30	630x670x30	580x670x30	525x670x30	480x670x30	380x670x30
Maximum power voltage (Vmp)	17.5V	17.5V	17.5V	17.5V	17.5V	17.5V
Maximum power current (Imp)	3.43A	3.143A	2.86A	2.57A	2.29A	1.72A
Open circuit voltage (Voc)	21.6V	21.6V	21.6V	21.6V	21.6V	21.6V
Short circuit current (Isc)	3.87A	3.55A	3.23A	2.9A	2.59A	1.93A
Cell efficiency	16.50%	16.50%	16.50%	16.50%	16.50%	16.50%
Maximum system voltage	DC 1000V					
Temp.Coeff.of Isc(TK Isc)	0.045%/°C					
Temp.Coeff.of Voc(TK Voc)	-0.34%/°C					
Temp.Coeff.of Pmax(TK Pmax)	-0.47%/°C					
Normal Operating Cell Temperature	45±2°C					
Tolerance	±3%					

STC Irradiance 1000W/m² , Temperature 25°C , AM=1.5

Specifications

Model type	SR 20-36P	SR 15-36P	SR 10-36P	SR 5-36P
Peak power(Pmax)	20W	15W	10W	5W
Weight	2.11kg	1.71kg	1.09kg	0.73kg
Dimensions(mm)	475x350x25	375x350x25	270x350x17	170x350x17
Maximum power voltage (Vmp)	17.5V	17.5V	17.5V	17.5V
Maximum power current (Imp)	1.15A	0.86A	0.58A	0.29A
Open circuit voltage (Voc)	21.6V	21.6V	21.6V	21.6V
Short circuit current (Isc)	1.3A	0.97A	0.65A	0.33A
Cell efficiency	16.50%	16.50%	16.50%	16.50%
Maximum system voltage	DC 1000V			
Temp.Coeff.of Isc(TK Isc)	0.045%/°C			
Temp.Coeff.of Voc(TK Voc)	-0.34%/°C			
Temp.Coeff.of Pmax(TK Pmax)	-0.47%/°C			
Normal Operating Cell Temperature	45±2°C			
Tolerance	±3%			

STC Irradiance 1000W/m² , Temperature 25°C , AM=1.5